

OIL-FLOODED SCREW NEXT II series 11-160kW



Asia & Oceania

China
Hitachi Industrial Equipment Systems (China) Co., Ltd.

(Shanghai Branch)
Room2201, Rui Jin Building, No.205
Maoming Road(S) Shanghai 200020
TEL : +86 (21) 5489-2378
FAX : +86 (21) 3356-5070

(Beijing Branch)
Room1420, Beijing Fortune Building,
No.5 Dong San Huan Bei Road,
Chao Yang District, Beijing 100004
TEL : +86 (10) 6590-8180
FAX: +86 (10) 6590-8189
(Guangzhou Branch)
Room3003, HNA Tower,
8# Linhezhong Road, Tianhe District,
Guangzhou 510610
TEL : +86 (20) 3877-0438
FAX: +86 (20) 2735-3820

Hitachi Industrial Equipment Systems (Hong Kong) Co., Ltd.

8/F, Building 20E, Phase 3, Hong Kong
Science Park, Pak Shek Kok,
New Territories, Hong Kong
TEL: +852 2735-9218
FAX: +852 2735-6793

Taiwan Hitachi Asia Pacific Co., Ltd

3rd Floor, No. 167, Tun Hwa N. Road,
Hung-Kuo Building, Taipei 10512, Taiwan
TEL : +886 (2) 2718-3666
FAX: +886 (2) 2514-7664

Indonesia

PT Hitachi Asia Indonesia
International Financial Centre Tower 2
39th floor Suite #03-04, Jl.
Jenderal Sudirman Kav 22-23,
Jakarta Selatan, 12920, Indonesia
TEL : +62 (21) 2528470
FAX : +62 (21) 2358 6755

Malaysia

Hitachi Asia (Malaysia) Sdn. Bhd.
Suite 17.3, Level 17, Menara IMC
(Letter Box No.5) No. 8 Jalan Sultan
Ismail, 50250, Kuala Lumpur
TEL : +60 (3) 2031-8751
FAX: 160 (3) 2031-8758

Philippines

Hitachi Asia Ltd. Philippine Branch
Unit 8, 11th Floor Zuellig Bldg.,
Makati Avenue corner Paseo de Roxas
Makati City, Philippines 1225
TEL: +632 886-9018
FAX: +632 887-3794

Singapore

**Hitachi Asia Ltd.
(Industrial Components & Equipment
Group)**
7 Tampines Grande, #08-01
Hitachi Square, Singapore 528736
TEL: +65-6305-2100
FAX: +65-6305-2100

Thailand

Hitachi Asia (Thailand) Co., Ltd.
12th Floor, Ramaland Bldg., No.952,
Rama IV Road, Suriyawongse, Bangrak,
Bangkok 10500, Thailand
TEL : +66 (2) 632-9292
FAX: +66 (2) 632-9299

Viet Nam

**Hitachi Asia Ltd.
(Ho Chi Minh City Office)**
Room 8-9-10A 4th Floor, The Landmark,
5B Ton Duc Thang Street, Ben Nghe Ward,
District 1, Ho Chi Minh City, Vietnam
TEL: +84 (8) 3829-9725
FAX: +84 (8) 3829-9729
(Ha Noi Office)
Room 2302, 23th West, Lotte Center,
54 Lieu Giai street, Cong Vi Ward,
Ba Dinh District, Hanoi, Vietnam
TEL: +84 (4) 3933-3123
FAX: +84 (4) 3933-3125

Hitachi Global Air Power (Changshu) Co., Ltd.

For more information, please consult Hitachi dealer nearest to you.

Due to product improvements, the specifications, appearance, etc. of the samples described in the manual are subject to change without notice. The samples are presented in printed form and sometimes slightly different from actual products in color.




Hitachi – A Trusted Expert in Air Compressors

With a history of more than a century, Hitachi Compressor has always treated 100% customer satisfaction as the source of enterprise development.

As the leading compressor manufacturer in Japan, we are committed to continuous technological innovation and development of air compressors to meet each customer's requirements. Our products are available in power from 0.2kW to 770kW and types of piston, scroll, screw, etc.

Hitachi can provide customers with the most suitable compressed air systems in both oil and oil-free applications.

We believe, with our high-quality and efficient air compressor products, multiple compressed air solutions and perfect pre-sales and after-sales services, Hitachi will become your most trusted compressed air expert.




Ultimate evolution of air compressor - OSP NEXT II series

We are proud to introduce **OSP NEXT II series**, a new milestone in Hitachi innovation of air compressor technology.

With outstanding reliability, premium efficiency and industry leading performance, **OSP NEXT II series** will undoubtedly match your requirements for air compressors.



History of Hitachi Air Compressor



Model list

| Model | | Nominal Output (kW) | | | | | | | | | |
|---------------------|---------------|---------------------|----|----|----|----|----|-----|-----|-----|---|
| | | 11 | 15 | 22 | 37 | 55 | 75 | 110 | 132 | 160 | |
| Variable speed type | VPLUS (Vtype) | Air-cooled | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| | | Water-cooled | | | | | ○ | ○ | ○ | | ○ |
| Fixed speed type | Mtype | Air-cooled | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| | | Water-cooled | | | | | ○ | ○ | ○ | ○ | ○ |

OSP NEXT II series

Hitachi Aired

High-performance

The rotor profile designed by Hitachi provide high performance and high efficiency.



All-in-one structure

The integral structure of the oil separator and the aired reduces the pressure loss and minimizes the energy loss.(22/37kW Vplus)



22/37kW Vplus Aired

Directly-coupled design

No transmission loss by the directly-coupled design of the high-efficient DCBL motor and the aired.(22-75kW Vplus)



55/75kW Vplus Aired



Intelligent control


Rapid Air Blow-Off Control

"NEW HISCREW OIL NEXT" is the new synthesis oil which hardly foams during oil case air pressure releasing. This achieves shorten blow-off time, and as a result, both auto stop time and unloading time shorten. This rapid blow-off control prevents a pressure drop when the air consumption is increased when the air compressor is automatically stopped.



Constant pressure control

Since Constant Pressure Control allows highly precise pressure control within range of $\pm 0.01\text{MPa}$, supply of compressed air at necessary pressure is possible with high efficiency.



Long term maintenance cycle & easy maintenance

Package Filter as standard

The filter is mounted on the air intake of the air compressor as standard. The touch panel shows maintenance indication according to the set value.



Oil Separator Element

Spin-on type filter is adopted with excellent maintenance. It employs a large oil separator element, delivers a stable oil separation performance.



Large Air Intake Filter

Cartridge type filter is used for easy replacement. The two-stage method of inertial separation and special designed media improves filtration efficiency.



Hitachi DCBL Motor

Energy-saving


DCBL Controller

Retry function as standard


Retry function is available for the occasion of minor failures of controller. The compressor can retry up to three times with its own function in case of controller trip. So, it is possible to eliminate the influence to the operation of the compressor from outside disturbance.

Cascade Vector Control


By adding Vector Control in a line from Cascade to the normal DCBL control, both high efficiency and high reliability are achieved.



The difference between permanent magnet motor and induction motor



Example of energy saving in variable speed compressor



Before installation

- Average load rate: 52%
- Power consumption 23,600 kWh/month

After installation

- 37 kW variable speed compressor × 1 unit installed
- Reduction in power consumption: **34%**(Calculated value)

Note: Before installation, energy saving diagnosis was performed on the existing model(37kW fixed speed compressor x 1 unit).




**More Efficiency
Fit to Improve Productivity
Higher Level of User-friendly**

NEXT II series

High Reliability

Up to 50°C

- Standard up to 45°C
- Operation is possible under 50°C



Ambient temperature alarm will be indicated when ambient temperature is over 45°C. Continuous operation at higher than 45°C may shorten lifetime of lubricating oil and electric parts.

NEW HISCREW OIL NEXT

- Designed for screw air compressor.
- Oil change cycle is every 2 years or 12,000hr which comes first.



Overhaul Cycle 11-75kW - 8 years 110-160kW - 6 years

The overhaul cycle of Airend is every 6-8 years, since the combination of high-performance bearing and high-precision oil filtration system is adopted.



*Condition : 6,000hr or less Operation Time ,
Overhaul cycle for 1.0MPa specification machine is 4 years.


Versatility in Hitachi original Technology

PQ WIDE MODE

PQ WIDE MODE, by automatically adjusting the maximum rotation speed of the compressor, enables to increase the discharge FAD in case that the pressure declines. Compared to conventional VSD, compressor is possible to operate at a wider range of pressure (P) and FAD (Q)

FAD at PQ WIDE MODE

| Model | Discharge Pressure MPa | Air Consumption Ratio (%) | | | | | | |
|-------|------------------------|---------------------------|------|------|------|------|------|------|
| | | 0.45 | 0.50 | 0.60 | 0.70 | 0.85 | 0.90 | 0.95 |
| 11kW | - | 1.79 | 1.79 | 1.79 | 1.63 | 1.53 | - | - |
| 15kW | - | 2.4 | 2.4 | 2.4 | 2.15 | 2.04 | - | - |
| 22kW | 4.3 | 4.3 | 4.3 | 4.1 | 3.6 | - | - | - |
| 37kW | 7.1 | 7.1 | 7.1 | 6.8 | 6.2 | - | - | - |
| 55kW | 10.6 | 10.6 | 10.6 | 10.1 | 9.1 | - | - | - |
| 75kW | 14.0 | 14.0 | 14.0 | 13.3 | 12.0 | - | - | - |
| 110kW | 22.5 | 22.5 | 22.5 | 21.5 | 19.3 | - | - | - |
| 160kW | 29.5 | 29.5 | 29.5 | 29.5 | 26.9 | 26.0 | 25.2 | - |



IPC Control (Intelligent Pressure Control)

VPLUS M type

By estimating use point pressure in accordance with air consumption, IPC control decreases discharge pressure during low load operation, which enables Energy-Saving.

Patent JP4425768 and others


Example of effect by IPC

- Conditions
- Air compressor: OSP-37VAN2
 - Control pressure setting: 0.70MPa
 - Use point pressure during full load: 0.55MPa
 - Piping pressure loss during full load: 0.15MPa

Graph of pressure change (Theoretical values)



① IPC-OFF (Conventional inverter control model)

- Control the air compressor discharge pressure at 0.70MPa



② IPC-ON (NEXT II series)

- Control the use point pressure at 0.55MPa



*Due to estimation control, use point pressure varies in accordance with use conditions.

Multi-Function Touch Screen*

- Significant Improvement of User-friendly
- Various Functions Available
- Operation Data Logging

Main Functions

- Schedule Operation (Weekly Timer)
- Instantaneous Power Interruption (IPI) Restart Function
- Alternate Operation (Option)
- Multi-unit Control (Option)
- AUTO Operation
- Communication Function
- Web Server Function
- Display/Store of Operation Data
- Store/Load of Settings
- Maintenance Time Notification
- Operation Data Memory, Display in Graph
- Display of Shutdown and Alarm History

*The image described above has been modified.

*IT communication function is only for 22kW or bigger models with touch screen. Touch screen less option is available for OSP-22/37MAN2.

IT Communication Functions*

USB Flash Memory Possible for Data Logging

*Necessary to prepare a USB flash memory device (5.5 cm or smaller) on user's side.
*Operation data for one day is approximately 400KB. (For reference)

Web Server Function via Bluetooth®


*Necessary to prepare a Bluetooth® USB dongle on your side.
*For setting changes, part of the items are applicable.

Modbus® Communication

Open network serial communication Modbus®/RTU is supported as standard

*Modbus®/TCP support is optional.

*IT communication function is only for 22kW or bigger models with touch screen. Touch screen less option is available for OSP-22/37MAN2.




The image described above has been modified.

• Bluetooth is the registered trademark of Bluetooth SIG Inc. (US).
• Modbus is the registered trademark of Schneider Automation Inc.

Auxiliary Equipment

Example of Oil-Flooded Screw Compressed Air System



1 Air Receiver Tank

In order to exert the energy saving effect of compressor, Hitachi recommend to choose the air receiver tank with following volume.

Air Receiver Tank volume list

| kW | Model | Mtype | | VPLUS |
|-----|-------|----------|---------|-------|
| | | Standard | ECOMODE | |
| 11 | | 0.15 | 0.28 | 0.15 |
| 15 | | 0.28 | 0.43 | 0.28 |
| 22 | | 0.43 | 0.70 | 0.43 |
| 37 | | 0.70 | 1.24 | 0.43 |
| 45 | | 0.70 | 1.24 | - |
| 55 | | 1.24 | 1.24 | 0.70 |
| 75 | | 1.24 | 2.26 | 1.24 |
| 110 | | 2.26 | 4.0 | 4.0 |
| 132 | | 4.0 | 8.0 | 4.0 |
| 160 | | 4.0 | 8.0 | 4.0 |

Note : For detail information of above auxiliary equipment, contact your nearest dealer or Hitachi local representative office

2 Air Dryer

- Dry air of higher quality
- A rich line-up for your choice

3 Line Filter

- Various types of filter
(Air Filter, Micro-Mist Filter, Activated Carbon Filter)

4 Multi Unit Control Panel


MULTI ROLLER *G* series

- Energy-saving
- Easy-to-read LCD touch screen equipped


VPLUS's energy-saving solutions

Energy-saving solution

To respond to the change in air demand, connect VPLUS and Mtype, Hitachi provide three patterns of system structure to help you acquire energy-saving.




■ V-M combination Type



■ Single-V (Multi-V) Multi-Unit control System

Multi-Unit control Panel MULTI ROLLER *G* series
OSP VPLUS + OSP Mtype



Standard Specification Sheet (Vtype)

11-37kW Vtype

| Item ·Unit | Model | OSP-11VAN2-L | OSP-15VAN2-L | OSP-22VAN2 | OSP-37VAN2 |
|------------------------------------|------------------------|---|--------------|-----------------------------|-------------------|
| Cooling Method | – | Air-Cooled | | | |
| Nominal Output | kW | 11 | 15 | 22 | 37 |
| Rated | Discharge Pressure | 0.85 | | | |
| | Discharge Air Capacity | 1.63 | 2.15 | 4.1 | 6.8 |
| PQ WIDE MODE | Discharge Pressure | 0.7 | 0.9 | 0.7 | 0.9 |
| | Discharge Air Capacity | 1.79 | 1.53 | 2.4 | 2.04 |
| Intake Air Pressure/Temperature | – | Atmospheric Pressure / 0 to 45°C | | | |
| Discharge Air Temperature | °C | Atmospheric Temperature + 15°C or below | | | |
| Driving Method | – | 4-pole TEFC motor with V-Belt Drive | | DCBL Direct Drive | |
| Starting Method | – | Soft Start | | | |
| Lubricating Oil | – | NEW HISCREW OIL NEXT | | | |
| Lubricating Oil Quantity | L | 6 | 7 | 10 | 15 |
| Nominal Output of Cooling Fan | kW | 1.5 (with Inverter Control) | | 1.5 (with Inverter Control) | |
| Discharge Pipe Diameter | – | RC1 | | RC1-1/2 | |
| Dimension (WxDxH) | mm | 950x780x1,250 | | 1,000x1,050x1,550 | 1,200x1,150x1,650 |
| Weight | kg | 350 | 372 | 450 | 670 |
| Recommended Air Receiver Volume | m ³ | 0.15 or bigger | | 0.28 or bigger | |
| Noise Level (1.5m from front side) | dB(A) | 58 | 61 | 56 | 60 |

55-75kW Vtype

| Item ·Unit | Model | OSP-55VAN2 | OSP-75VAN2 | OSP-55VWN2 | OSP-75VWN2 |
|------------------------------------|------------------------|---|-----------------------------|---|----------------|
| Cooling Method | – | Air-Cooled | | Water cooled | |
| Nominal Output | kW | 55 | 75 | 55 | 75 |
| Rated | Discharge Pressure | 0.7 | | | |
| | Discharge Air Capacity | 10.1 | 13.3 | 10.1 | 13.3 |
| PQ WIDE MODE | Discharge Pressure | 0.6 | 0.85 | 0.6 | 0.85 |
| | Discharge Air Capacity | 10.6 | 9.1 | 14.0 | 12.0 |
| Intake Air Pressure/Temperature | – | Atmospheric Pressure / 0 to 45°C | | | |
| Discharge Air Temperature | °C | Atmospheric Temperature + 15°C or below | | Atmospheric Temperature + 13°C or below | |
| Driving Method | – | DCBL Motor with Coupling | | | |
| Starting Method | – | Soft Start | | | |
| Lubricating Oil | – | NEW HISCREW OIL NEXT | | | |
| Lubricating Oil Quantity | L | 26 | 36 | 17 | 24 |
| Nominal Output of Cooling Fan | kW | 1.5 (with Inverter Control) | 2.2 (with Inverter Control) | 0.05 X 2 | |
| Discharge Pipe Diameter | – | Rc2 | | | |
| Dimension (WxDxH) | mm | 2,000 x 1,200 x 1,800 | | | |
| Weight | kg | 1,230 | 1,405 | 1,070 | 1,240 |
| Recommended Air Receiver Volume | m ³ | 0.7 or bigger | 1.24 or bigger | 0.7 or bigger | 1.24 or bigger |
| Cooling water | °C | 35 or below | | | |
| | L/min | | | 100 | 125 |
| Cooling water pipe diameter | – | Rc2 | | | |
| Noise Level (1.5m from front side) | dB(A) | 64 | 66 | 63 | 65 |

110-160kW Vtype

| Item ·Unit | Model | OSP-110VAN2 | OSP-160VAN2 | OSP-110VWN2 | OSP-160VWN2 |
|------------------------------------|------------------------|---|---------------------------------|---|-----------------------|
| Cooling Method | – | Air-Cooled | | Water cooled | |
| Nominal Output | kW | 110 | 160 | 110 | 160 |
| Rated | Discharge Pressure | 0.7 | | | |
| | Discharge Air Capacity | 21.5 | 29.5 | 21.5 | 29.5 |
| PQ WIDE MODE | Discharge Pressure | 0.6 | 0.85 | 0.6 | 0.85 |
| | Discharge Air Capacity | 22.5 | 19.3 | 25.2 | 22.5 |
| Intake Air Pressure/Temperature | – | Atmospheric Pressure / 0 to 45°C | | | |
| Discharge Air Temperature | °C | Atmospheric Temperature + 15°C or below | | Atmospheric Temperature + 13°C or below | |
| Driving Method | – | 4-Pole TEFC Motor with Gear Driving | | | |
| Starting Method | – | Soft Start | | | |
| Lubricating Oil | – | NEW HISCREW OIL NEXT | | | |
| Lubricating Oil Quantity | L | 50 | 115 | 37 | 70 |
| Nominal Output of Cooling Fan | kW | 1.5 x 2 (with Inverter Control) | 4.0 x 2 (with Inverter Control) | 0.05 x 3 | 0.2 |
| Discharge Pipe Diameter | – | 2-1/2 in | 3 in | 2-1/2 in | 3 in |
| Dimension (WxDxH) | mm | 2,550 x 1,500 x 1,800 | 2,700 x 2,000 x 1,890 | 2,550 x 1,500 x 1,800 | 2,700 x 2,000 x 1,890 |
| Weight | kg | 2,900 | 3,900 | 2,800 | 3,750 |
| Recommended Air Receiver Volume | m ³ | 4.0 or bigger | | | |
| Cooling water | °C | 35 or below | | | |
| | L/min | | | 180 | |
| Cooling water pipe diameter | – | Rc2 | | | |
| Noise Level (1.5m from front side) | dB(A) | 75 | 79 | 72 | |

- Capacity is measured according to ISO 1217, Annex C.
- Discharge pressure is gauge pressure.
- Temperature of discharge air may vary from different environments.
- For Vtype/PLUS, when PQ wide mode is ON, it may be necessary to increase the size of the separate dryer, filter, etc. Please contact your nearest Hitachi sales representative.
- Be sure to install an air tank with more than the recommended capacity. For Mtype (constant speed compressor) to maximize (ECOMODE) energy efficiency, use air receiver tank which is recommended.
- Earth leakage breaker is not built in the compressor. Prepare by customer.
- Grounding must be used separately.

Standard Specification Sheet (Mtype)

11-37kW Mtype

| Item ·Unit | Model | OSP-11MA5AN2-L | OSP-15M5AN2-L | OSP-22M5AN2(-L) | OSP-37M5AN2(-L) |
|------------------------------------|------------------------|---|----------------|-------------------|-------------------|
| Cooling Method | – | Air-Cooled | | | |
| Nominal Output | kW | 11 | 15 | 22 | 37 |
| Rated | Discharge Pressure | 0.85 <0.7> | 0.85 <0.7> | 0.7 <0.85>[1.0] | 0.7 <0.85>[1.0] |
| | Discharge Air Capacity | 1.63 <1.79> | 2.15 <2.4> | 4.0 <3.7>(3.3) | 7.2 <6.6>(5.8) |
| Intake Air Pressure/Temperature | – | Atmospheric Pressure / 0 to 45°C | | | |
| Discharge Air Temperature | °C | Atmospheric Temperature + 15°C or below | | | |
| Driving Method | – | 4-pole TEFC motor with V-Belt Drive | | | |
| Starting Method | – | Direct Connection/Star-Delta | | Star-Delta | |
| Lubricating Oil | – | NEW HISCREW OIL NEXT | | | |
| Lubricating Oil Quantity | L | 6 | 7 | 10 | 15 |
| Nominal Output of Cooling Fan | kW | 1.5 (with Inverter Control) | | | |
| Discharge Pipe Diameter | – | Rc1 | | RC1-1/2 | |
| Dimension (WxDxH) | mm | 950x780x1,250 | | 1,000x1,050x1,550 | 1,200x1,150x1,650 |
| Weight | kg | 345 | 357 | 670 | 970 |
| Recommended Air Receiver Volume | m ³ | 0.15 or bigger | 0.28 or bigger | 0.43 or bigger | 0.7 or bigger |
| Noise Level (1.5m from front side) | dB(A) | 58 | 61 | 57 | 60 |

55-75kW Mtype

| Item ·Unit | Model | OSP-55MAN2 | OSP-75MAN2 | OSP-55MWN2 | OSP-75MWN2 |
|------------------------------------|------------------------|---|-----------------------------|---|------------------|
| Cooling Method | – | Air-Cooled | | Water cooled | |
| Nominal Output | kW | 55 | 75 | 55 | 75 |
| Rated | Discharge Pressure | 0.7 <0.85>[1.0] | | | |
| | Discharge Air Capacity | 10.0-9.0>[8.3] | 13.2<11.9>(10.9) | 10.0-9.0>[8.3] | 13.2<11.9>(10.9) |
| Intake Air Pressure/Temperature | – | Atmospheric Pressure / 0 to 45°C | | | |
| Discharge Air Temperature | °C | Atmospheric Temperature + 15°C or below | | Atmospheric Temperature + 13°C or below | |
| Driving Method | – | 2-pole TEFC motor with Gear Driving | | | |
| Starting Method | – | Star-Delta | | | |
| Lubricating Oil | – | NEW HISCREW OIL NEXT | | | |
| Lubricating Oil Quantity | L | 27 | 38 | 17 | 24 |
| Nominal Output of Cooling Fan | kW | 1.5 (with Inverter Control) | 2.2 (with Inverter Control) | 0.05 X 2 | |
| Discharge Pipe Diameter | – | Rc2 | | | |
| Dimension (WxDxH) | mm | 2,000 x 1,200 x 1,800 | | | |
| Weight | kg | 1,520 | 1,800 | 1,360 | 1,640 |
| Recommended Air Receiver Volume | m ³ | 1.24 or bigger | | | |
| Cooling water | °C | 35 or below | | | |
| | L/min | | | 100 | 125 |
| Cooling water pipe diameter | – | Rc2 | | | |
| Noise Level (1.5m from front side) | dB(A) | 65 | 67 | 64 | 66 |

110-160kW Mtype

| Item ·Unit | Model | OSP-110MAN2 | OSP-132MAN2 | OSP-160MAN2 | OSP-110MWN2 | OSP-132MWN2 | OSP-160MWN2 |
|------------------------------------|------------------------|---|---------------------------------|------------------|---|-----------------------|------------------|
| Cooling Method | – | Air-Cooled | | | Water cooled | | |
| Nominal Output | kW | 110 | 132 | 160 | 110 | 132 | 160 |
| Rated | Discharge Pressure | 0.7 <0.85>[1.0] | | | | | |
| | Discharge Air Capacity | 21.5<20.4>[17.0] | 25.5<23.3>[21.0] | 29.5<27.2>[24.5] | 21.5<20.4>[17.0] | 25.5<23.3>[21.0] | 29.5<27.2>[24.5] |
| Intake Air Pressure/Temperature | – | Atmospheric Pressure / 0 to 45°C | | | | | |
| Discharge Air Temperature | °C | Atmospheric Temperature + 15°C or below | | | Atmospheric Temperature + 13°C or below | | |
| Driving Method | – | 4-Pole TEFC Motor with Gear Driving | | | | | |
| Starting Method | – | Star-Delta | | | | | |
| Lubricating Oil | – | NEW HISCREW OIL NEXT | | | | | |
| Lubricating Oil Quantity | L | 50 | 105 | 115 | 37 | 65 | 70 |
| Nominal Output of Cooling Fan | kW | 1.5 x 2 (with Inverter Control) | 4.0 x 2 (with Inverter Control) | | 0.05 x 3 | 0.2 | |
| Discharge Pipe Diameter | – | 2-1/2 in | 3 in | | 2-1/2 in | 3 in | |
| Dimension (WxDxH) | mm | 2,550 x 1,500 x 1,800 | 2,700 x 2,000 x 1,890 | | 2,550 x 1,500 x 1,800 | 2,700 x 2,000 x 1,890 | |
| Weight | kg | 2,800 | 3,450 | 3,600 | 2,700 | 3,300 | 3,420 |
| Recommended Air Receiver Volume | m ³ | 2.0 or bigger | 4.0 or bigger | | 2.0 or bigger | 4.0 or bigger | |
| Cooling water | °C | 35 or below | | | | | |
| | L/min | | | 180 | | | |
| Cooling water pipe diameter | – | Rc 2 | | | | | |
| Noise Level (1.5m from front side) | dB(A) | 75 | 77 | 79 | 72 | 72 | 72 |

- Do NOT use any oil other than "NEW HISCREW OIL NEXT."
- If the voltage imbalance ratio exceeds 1% during rated load operation, or if the power transformer capacity is more than 10 times the motor output and exceeds 500 kVA, an AC reactor needs to be installed between the power and the air compressor to regulate and improve the power.
- Install the air compressor indoors and avoid flammable and corrosive environment, moisture and dust.
- Appearance and specifications are subject to change without notice.
- Noise level is the converted value under the condition of 1.5m in front, 1m height, at full load running in an anechoic room. It may vary depending on capacity control and installation environment. For Vtype/PLUS, noise level may be increased by 3dB when PQ WIDEMODE is ON. It will be higher than indicated value in actual field installations with echo. It is not a guaranteed value.
- < > [] show values of capacity under different discharge pressures.
- 1.0 MPa model is ONLY available on 22/37/55/75kW Mtype. For details, contact your nearest Hitachi sales representative.
- IT communication function is only for 22kW or bigger models with touch screen. Touch screen less option is available for OSP-22/37MAN2.